

1120

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

· Watertight, crushproof, and dustproof

- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck[™] with convoluted lid foam
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1120 Standard



1120NF No Foam



1120WF With Foam

DIMENSIONS

Interior (L×W×D) 7.29 x 4.78" x 3.33 (18.5 x 12.1 x 8.5 cm) Exterior (L×W×D) 8.41 x 6.76" x 3.87 (21.4 x 17.2 x 9.8 cm)

 Lid Depth
 0.50" (1.3 cm)

 Bottom Depth
 2.56" (6.5 cm)

 Total Depth
 3.06" (7.8 cm)

 Int Volume
 0.07 ft³ (0.002 m³)

MATERIALS

Body Polypropylene
Latch Polypropylene
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS



Orange

Yellow

WEIGHT

 Weight With Foam
 1.43 lbs (0.6 kg)

 Weight Empty
 1.34 lbs (0.6 kg)

 Master Pack Weight
 10.45 lbs (4.7 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

IP67

Def Stan 81-41 STANAG 4280

OTHER

Master Pack6Militaryyes

ACCESSORIES



1121 3 pc. Replacement Foam Set



1123 Replacement O-ring



1120PFSpecial Application Panel Frame



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel